

Using Structural Equation Modelling (SEM) to Understand the Relationships among Critical Success Factors (CSFs) for Stakeholder Management in Construction

Citation for published version:

Molwus, JJ, Erdogan, B & Ogunlana, SO 2017, 'Using Structural Equation Modelling (SEM) to Understand the Relationships among Critical Success Factors (CSFs) for Stakeholder Management in Construction', *Engineering Construction and Architectural Management*, vol. 24, no. 3, pp. 426-450.
<https://doi.org/10.1108/ECAM-10-2015-0161>

Digital Object Identifier (DOI):

[10.1108/ECAM-10-2015-0161](https://doi.org/10.1108/ECAM-10-2015-0161)

Link:

[Link to publication record in Heriot-Watt Research Portal](#)

Document Version:

Peer reviewed version

Published In:

Engineering Construction and Architectural Management

General rights

Copyright for the publications made accessible via Heriot-Watt Research Portal is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

Heriot-Watt University has made every reasonable effort to ensure that the content in Heriot-Watt Research Portal complies with UK legislation. If you believe that the public display of this file breaches copyright please contact open.access@hw.ac.uk providing details, and we will remove access to the work immediately and investigate your claim.



**Using Structural Equation Modelling (SEM) to Understand
the Relationships among Critical Success Factors (CSFs) for
Stakeholder Management in Construction**

Journal:	<i>Engineering, Construction and Architectural Management</i>
Manuscript ID	ECAM-10-2015-0161.R3
Manuscript Type:	Original Article
Keywords:	Construction, Critical success factors, stakeholder management, Structural Equations Modelling, Project sucess, Relationships
Abstract:	

SCHOLARONE™
Manuscripts

Review

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

1 **Using Structural Equation Modelling (SEM) to Understand the Relationships among**
2 **Critical Success Factors (CSFs) for Stakeholder Management in Construction**

3 **ABSTRACT**

4 **Purpose** – Stakeholder management plays a significant role in the successful delivery of
5 construction projects. However, being able to carry out effective stakeholder management in
6 construction is contingent upon understanding the interrelationships among the critical
7 success factors (CSFs) for stakeholder management in construction and how they are related
8 to project success. This would enable the persons responsible for stakeholder management to
9 know the logical process for addressing the critical success factors in order to get stakeholder
10 management right. The understanding of this relationship has not been addressed. This
11 research aimed to investigate the interrelationships between the CSFs for stakeholder
12 management and project success in construction.

13 **Design/Methodology/Approach** – From an extensive literature review, 23 critical success
14 factors for stakeholder management in construction were identified. A conceptual structural
15 equation model (SEM) of the relationships between critical success factors was developed
16 (including measurement and structural models) using the groupings of the critical success
17 factors for stakeholder management in construction. A questionnaire survey was used to
18 collect data from construction industry practitioners. The data so collected were analysed
19 using SEM in Analysis of Moment Structures (AMOS).

20 **Findings** – The SEM analysis of data collected resulted in the best fitting measurement
21 model comprising 16 critical success factors as indicators of four latent variables namely,
22 stakeholder characteristics and project characteristics; stakeholder analysis; stakeholder
23 dynamics; and stakeholder engagement/empowerment. Furthermore, it was found that only
24 stakeholder engagement/empowerment has direct positive impact on project success. The

other three constructs stakeholder characteristics and project characteristics, stakeholder analysis and understanding stakeholder dynamism collectively impact on project success through the construct, stakeholder engagement/empowerment.

Research Limitations/Implications – The research reported in this paper was carried out in the UK hence the findings may have portrayed the UK construction professionals' opinion. However, the theoretical principles on which the research was based are general and similar research could be replicated in different countries whose construction procurement processes and industries are structured like those of the UK or otherwise.

Originality/Value – ~~The paper contributes to theory by empirically identifying the interrelationships among the critical success factors for stakeholder management linking to project success which will serve as a guide to construction professionals.~~ The main contribution of this study to existing knowledge is an empirical evidence of the interrelationships among the CSFs for stakeholder management in construction through their latent variables which is portrayed in the best fitting structural model showing the relationships between the constructs of CSFs for stakeholder management and project success. This should serve as a guide to construction project management team or responsible professionals for undertaking stakeholder management in construction projects.

Keywords – construction, stakeholder management, Critical success factors, Project success, Relationship, structural equation modelling

Paper type – Research paper

INTRODUCTION

Despite continuous efforts aimed at improving project success in the construction industry, it has seldom been a common occurrence for construction projects to be

1
2
3
4
5
6
7 48 successfully delivered. Construction projects are generally unique in nature due to their
8
9 49 processes and interaction with numerous parties within and around them. Construction
10
11 50 projects are traditionally divided into a series of activities undertaken by different individuals
12
13 51 or groups who may have different levels of interest and or involvement in the project (Egan,
14
15 52 1998). Just like any other venture, they are constrained by time and resources which are
16
17 53 needed for the projects to be delivered successfully (Ibrahim and Nissen, 2003; Bourne,
18
19 54 2005). The lengthy process of design and execution of construction projects constitutes a
20
21 55 complex system which involves interactions, collaboration and negotiations among many
22
23 56 stakeholders which include but are not limited to the clients, designers, contractors, local
24
25 57 authorities and the general project environment (Cheeks, 2003; Winch 2010). Some
26
27 58 individuals or groups (such as labour unions, employers' association, general public, the
28
29 59 media, and institutional forces/nationalised industries (professional bodies) etc) may not be
30
31 60 directly involved in the project but may have interest in and could have the power and be
32
33 61 capable of influencing the project delivery process (Leung and Olomolaiye, 2010). All parties
34
35 62 involved directly or indirectly in the project are referred as the project stakeholders.
36
37 63 Satisfying the dynamic expectations of project stakeholders throughout the life cycle of the
38
39 64 project is instrumental to the successful completion of construction projects (Atkin and
40
41 65 Skitmore, 2008). This can be achieved through stakeholder management. Stakeholder
42
43 66 management on projects should be carried out in order to obtain the support and contributions
44
45 67 of stakeholders as much as possible towards the project and achieve the best possible results
46
47 68 and project success (Black, 1995; Akintoye *et al.* 2003; Bourne, 2005; Olander and Landin,
48
49 69 2008; Jepsen and Eskerod, 2009). In the UK, client and stakeholder satisfaction is considered
50
51 70 as one of the main performance indicators of construction projects and construction projects
52
53 71 are now expected to be delivered to meet social value, sustainability and consideration of all
54
55 72 stakeholders' interests and needs (Winch, 2010).
56
57
58
59
60

1
2
3
4
5
6
7 73 The origin of stakeholder management theory has been attributed to Freeman's (1984)
8
9 74 book – "*Strategic Management: A Stakeholder Approach*". Stakeholder management is
10
11 75 concerned with the interrelationships between organisations and their diverse stakeholders
12
13 76 which can impact the project as well as individual parties and organisations associated with
14
15 77 the project both positively and negatively. Hence the aim of stakeholder management is for
16
17 78 organisations to identify, analyse, understand and effectively manage their stakeholders
18
19 79 (Chinyio and Olomolaiye, 2010). Although it started as a business management concept, the
20
21 80 theory of stakeholder management has been increasingly applied across different fields
22
23 81 including construction management. However, due to the peculiarity of construction projects
24
25 82 and process, it is necessary to device construction specific stakeholder management
26
27 83 principles.

28 84 Previous research efforts have investigated how stakeholder management in
29
30 85 construction projects can be improved focusing on different aspects of stakeholder
31
32 86 management in construction projects (Bourne and Walker, 2005; Chinyio and Akintoye,
33
34 87 2008). Most recently, Yang *et al.* (2009) and Yang and Shen (2014) developed a framework
35
36 88 for successful stakeholder management in construction projects based on the exploratory
37
38 89 groupings of the CSFs for stakeholder management. However, the exploratory groupings of
39
40 90 CSFs in Yang *et al.*'s, framework did not measure the interrelationships among the
41
42 91 constructs, the knowledge of which is needed to inform a logical stakeholder management
43
44 92 process in construction projects. Factor analysis is used to reduce a large number of related
45
46 93 variables into a manageable number of factors but to understand the interrelationships among
47
48 94 the factors, other more advanced multivariate analyses techniques need to be used as factor
49
50 95 analyses is not able to do so (Pallant, 2007). Furthermore, among the CSFs used in Yang *et*
51
52 96 *al.*'s framework, CSFs such as the use of appropriate procurement routes and adoption of
53
54 97 flexible project organisation were not considered. Therefore, there is need to empirically
55
56
57
58
59
60

1
2
3
4
5
6
7 98 investigate the interrelationships among the CSFs for stakeholder management in
8
9 99 construction. Moreover, how the CSFs for stakeholder management in construction projects
10
11 100 are related to project success is yet to be understood. Understanding these will enable project
12
13 101 management team to effectively carry out stakeholder management and achieve project
14
15 102 success. But what is project success?

16
17 103 The primary aim of carrying out stakeholder management in construction projects is
18
19 104 to deliver projects successfully. However, the perception of project success may not be that
20
21 105 straight forward. The word success can mean different things to different individuals and to
22
23 106 the same people in different circumstances or at different times (Bryde and Brown 2005;
24
25 107 Toor and Ogunlana 2008). The traditional perception of project success being judged based
26
27 108 on cost quality and time has changed over time to include stakeholder satisfaction, reduced
28
29 109 conflicts and disputes and environmental friendliness (Lim and Mohamed, 1999; Cookie-
30
31 110 Davies, 2002; Takim and Akintoye, 2002; Bryde and Brown 2005; Jugdev and Muller, 2005;
32
33 111 Toor and Ogunlana 2010). It now requires that KPIs are set and achieved through the project
34
35 112 in order for success to be attained (Chan and Chan 2004; Glenigan, 2011). Project success
36
37 113 (PS) factors therefore, encompass achieving the key success indicators of the project which
38
39 114 include: Timely completion of projects (PS1); on budget completion of projects (PS2);
40
41 115 completion to specified quality (PS3); and completion to stakeholders' satisfaction (PS4)
42
43 116 (Long *et al.*, 2004; Chan *et al.*, 2004; Jugdev and Muller, 2005).

44
45 117 The ~~level and effectiveness~~undertaking of stakeholder involvement at the inception of
46
47 118 the project and how it is sustained through the project life cycle has a big role in achieving
48
49 119 the KPI's of projects. An effective stakeholder management process depends on the
50
51 120 understanding of the CSFs for stakeholder management in construction projects (Yang *et al.*,
52
53 121 2009) as this will enable the project management team to ~~effectively~~successfully carry out
54
55 122 stakeholder management and achieve project success. Therefore, the research questions to be
56
57
58
59
60

1
2
3
4
5
6
7 123 answered in this study are: 1) How are the CSFs for stakeholder management in construction
8 124 projects interrelated? and 2) How are the CSFs for stakeholder management in construction
9 125 projects related to project success.
10
11

12
13 126 The research presented in this paper focussed on investigating the interrelationships
14 127 among the CSFs and aims to conceptualise and empirically test the measurement and
15 128 structural models of CSFs for stakeholder management in construction and how they are
16 129 related to project success. While, the measurement model is a representation of the
17 130 relationships between the CSFs and their constructs as well as the correlations/co-variations
18 131 among the constructs; the structural model is a representation of the causal interrelations
19 132 among the constructs of CSFs for stakeholder management in construction projects and how
20 133 they are related to project success. This paper presents reviews of CSFs for stakeholder
21 134 management in construction, the conceptual models (including measurement and structural
22 135 models) of CSFs for stakeholder management in construction, and presents the methodology
23 136 of the research, results and discussion before drawing conclusions.
24
25
26
27
28
29
30
31
32
33
34
35

36 137 **CRITICAL SUCCESS FACTORS (CSFS) FOR STAKEHOLDER MANAGEMENT** 37 38 138 **IN CONSTRUCTION**

39
40 139 For effective stakeholder management in construction projects, it is necessary to
41 140 identify and understand the interrelationships among the CSFs for stakeholder management.
42 141 Therefore, CSFs should be given constant and careful attention in stakeholder management in
43 142 construction being enablers of the process Critical success factors according to Rockart,
44 143 (1979) are “*areas, in which results, if they are satisfactory, will ensure successful competitive*
45 144 *performance for the organisation; they are the few key areas where things must go right for*
46 145 *the business to flourish*”. In other words, CSFs are actions, decisions, conditions or
47 146 circumstances in which the right things have to be done in order for the desired goals to be
48
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3
4
5
6
7 147 achieved in a project. A very important step for the study reported in this paper is the
8
9 148 identification of CSFs for stakeholder management in construction as they constitute the
10
11 149 measured attributes (indicators for the measurement model). . Past studies (Jepsen and
12
13 150 Eskerod, 2009; Olander and Landin, 2008; Chiyio and Akintoye, 2008; Jerges *et al.*, 2000)
14
15 151 have focused on identification of the factors which are critical to the success of stakeholder
16
17 152 management in construction projects. For example Olander and Landin, (2008) identified
18
19 153 four factors affecting stakeholder management process: Analysis of stakeholders' concern
20
21 154 and needs; communication of both potential benefits and negative impacts to stakeholders;
22
23 155 evaluation of alternative solutions; project organisation and relationship with the media.
24
25 156 Similarly, (Jerges *et al.*, 2000) suggested effective communication with stakeholders and
26
27 157 setting common goals and priorities among them for the project will improve stakeholder
28
29 158 management. Providing top level management support; responding to power interest
30
31 159 dynamism; maintaining existing relationship; being proactive with decisions; negotiations
32
33 160 and tradeoffs among others were considered necessary for successful stakeholder
34
35 161 management/engagement in construction projects (Chinyio and Akintoye, 2008).
36
37 162 Furthermore, Jepsen and Eskerod, (2009) found; stakeholder identification and classification
38
39 163 as well as predicting the expectations of stakeholders through stakeholder analysis to be
40
41 164 critical to stakeholder management process. The extensive literature review resulted in 23
42
43 165 critical success factors for stakeholder management in construction projects, which are
44
45 166 presented in Table 1 including the specific actions and decisions. These are all encompassing
46
47 167 factors which can vary from project to project and as the project progresses as a result of
48
49 168 which some CSFs may be omitted during some projects. Deciding which CSFs to omit, will
50
51 169 depend on project's organisation and mission among other things. These CSFs for
52
53 170 stakeholder management in construction were used to develop the conceptual model used in
54
55 171 this study based on the groupings by Molwus, *et al.* (2013) with slight modifications.
56
57
58
59
60

<Table 1>

**CONCEPTUAL MEASUREMENT AND STRUCTURAL MODELS OF CRITICAL
SUCCESS FACTORS FOR STAKEHOLDER MANAGEMENT IN CONSTRUCTION**

Identifying the critical success factors for stakeholder management in construction and grouping them are good initial steps towards successful stakeholder management in construction projects (Yang *et al.*, 2009). However, in order to further equip industry practitioners and ensure successful stakeholder management, the relationships between these success factors and their groupings should be clearly understood. This section presents a conceptual (theoretical) model of the interrelationships among the CSFs for stakeholder management in construction and their latent variables (constructs) drawn from the extant literature. The following underlying principles were used for development of the conceptual model:

1. Obtaining detailed information about the projects and its stakeholders is considered the first major step of stakeholder management which in turn informs stakeholder analysis (Chinyio and Akintoye, 2008; Yang *et al.*, 2009).
2. It is assumed being able to obtain such information entails knowing the characteristics of the project and its stakeholders.
3. The outcome of an informed stakeholder analysis/estimation would lead to the understanding of possible stakeholder dynamism and prediction of their likely behaviours on the basis of which appropriate stakeholder management/engagement strategies can be decided (Jepsen and Eskerod, 2009).

The measurement model consists of four constructs which were obtained by grouping the CSFs for stakeholder management grouped based on their related actions and the

1
2
3
4
5
6
7 196 stakeholder issues they aim to address (Molwus, *et al.*, 2013): Stakeholder characteristics and
8
9 197 project characteristics (SCPC); Stakeholder analysis (SA); Stakeholder dynamics (SD);
10
11 198 Stakeholder engagement/ empowerment (SE). The four constructs are individually and
12
13 199 collectively considered as enablers of stakeholder management and are measured by the CSFs
14
15 200 for stakeholder management in construction projects as shown in Table 2. The measurement
16
17 201 model proposes a positive correlation between the four constructs and direct positive
18
19 202 measurement of each construct by their indicators (Figure 1). The constructs and the
20
21 203 hypothesized relationships in the structural model are explained in the following subsections.
22
23 204 **Stakeholder Characteristics and Project Characteristics (SCPC)**
24
25 205 Clear understanding of projects' and stakeholders' characteristics would avail the
26
27 206 project management team sufficient information concerning the project and its stakeholders.
28
29 207 Project characteristics include size, location, type of client, funding source, procurement
30
31 208 issues, and objectives of the projects. Project characteristics as well as its potential impact
32
33 209 should be clearly identified and documented at the early stages of the project in order to
34
35 210 inform adequate stakeholder identification and analysis (Olander and Landin, 2005; Aaltonen
36
37 211 *et al.*, 2008; Jepsen and Eskerod, 2009). Stakeholder characteristics refer to stakeholders'
38
39 212 stakes and interests, bases of involvement (direct or indirect), sources of power and other
40
41 213 attributes (Mitchell, *et al.*, 1997; Winch, 2010). Without such information, it would be very
42
43 214 difficult to proceed with stakeholder management (Mitchell *et al.*, 1997; Bourne and Walker,
44
45 215 2005). Therefore, the conceptual measurement model hypothesised that stakeholder
46
47 216 characteristics and project characteristics is dependent upon the project management team's
48
49 217 ability to clearly formulate the project mission; adopt a favourable procurement route for the
50
51 218 project; carefully identify and list the project stakeholders; ensure the use of flexible project
52
53 219 organisation; and identifying and understanding stakeholder areas of interest.
54
55 220 Under this construct, the following hypotheses are stated:
56
57
58
59
60

221 *Hypothesis 1:* Obtaining adequate information on stakeholder characteristics and
222 project characteristics (SCPC) influences the impact of stakeholder management on
223 construction project success (PS).

224 *Hypothesis 2:* Obtaining adequate information on stakeholder characteristics and
225 project characteristics (SCPC) enables stakeholder analysis (SA).

226 *Hypothesis 3:* Obtaining adequate information on stakeholder characteristics and
227 project characteristics (SCPC) enables the understanding of stakeholder dynamism (SD).

228 **Stakeholder Analysis (SA)**

229 Stakeholder analysis consists of systematically determining stakeholders' areas and
230 levels of interests; expected contributions; expected levels of power and influence; and level
231 of importance; with respect to the project (Karlsen, 2002; Jepsen and Eskerod, 2009). It is
232 important for project managers or responsible professionals to analyse the powers, needs and
233 concerns of all project stakeholders, both internal and external to the project. If the needs and
234 concerns of project stakeholders are not carefully analysed and addressed, conflicts and
235 confrontations can arise among the stakeholders or between the stakeholders and the project
236 and consequently hamper the successful delivery of the project (Aaltonen *et al.*, 2008;
237 Olander and Landin, 2008; Li *et al.*, 2012). The results of stakeholder analysis will inform
238 and shape decisions on stakeholder management for the project hence will enhance the
239 likelihood of achieving success (Jepsen and Eskerod, 2009; Yang, 2014). Therefore, this
240 construct (latent variable) is hypothesised to be indicated by the project management's ability
241 to determine and assess stakeholders' attributes; appropriately classifying stakeholders
242 according to their attributes; predicting and mapping stakeholders' behaviours; predicting
243 stakeholders' potential influence on each other and on the project; and identifying and
244 analysing possible conflicts and coalition among stakeholders.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

245 Under this construct, the following hypotheses are stated:

246 *Hypothesis 4:* Stakeholder analysis (SA) influences the overall impact of stakeholder

247 | management on construction project success (PS).

248 Hypothesis 5: Stakeholder analysis (SA) enables effective stakeholder

249 engagement/empowerment (SE).

250 **Stakeholder Dynamics (SD)**

251 The stakes and interests of construction stakeholders can be as diverse as the

252 stakeholders themselves and these are dynamic over the life cycle of projects (Chinyio and

253 Akintoye, 2008). For example the primary interest of local residents is how the project affects

254 their amenity and immediate environment; local land owners are interested in making sure

255 that their interest will not be hurt by the project; the environmentalists are interested in

256 protecting the environment from pollution and or destruction; the competitors try to gain

257 competitive advantage by their actions; the media influence the perception of people about

258 the reputation of the project; and others include those whose connection to the project is not

259 immediately clear but whose support may be helpful to the success of the project (Leung and

260 Olomolaiye, 2010). These interests can change as the project progresses because

261 stakeholders’ ability to influence and control project decisions and actions depend on their

262 | level of power and other associated attributes in the project. ~~These~~ Furthermore, stakeholder

263 interests can change from stage to stage and even from time to time within the same stage

264 during the projects’ life cycle (Nash *et al.*, 2010). Unless appropriate strategies are adopted

265 for engaging and managing stakeholders based on their prevailing stance throughout the

266 project’s life cycle, they can spring up with surprises and hinder the progress of the project

267 (Olander and Landin, 2005). In order to adopt the appropriate strategy for engaging

268 stakeholders, it is necessary to understand the changing (dynamic) nature of stakeholders’

attributes during the project. It should be noted that understanding stakeholders' dynamism depends largely on careful stakeholder analysis (Aaltonen *et al.*, 2008). Therefore, this construct is indicated by project management's ability to effectively resolve conflicts among stakeholders; manage change of stakeholders' interest and influence; manage change of stakeholders' attributes; manage change of relationships among stakeholders; predict stakeholders' likely reaction for implementing project decisions and manage how project decisions affect stakeholders.

Under this construct, the following hypotheses are stated:

Hypothesis 6: Understanding stakeholder dynamism (SD) influences the overall impact of stakeholder management on construction project success (PS).

Hypothesis 7: Stakeholder analysis (SA) enables the understanding of stakeholder dynamism (SD).

Hypothesis 8: Understanding stakeholder dynamism (SD) enables effective stakeholder engagement/empowerment (SE).

Stakeholder Engagement/Empowerment (SE)

Given their dynamic nature and lengthy process of construction, stakeholders adopt different strategies at different stages of project to exert their interests on the project (Aaltonen *et al.*, 2008), hence different appropriate strategies should be used for engaging/managing stakeholders at different stages of the project depending on the prevailing circumstances. Using the most appropriate strategies for engaging project stakeholders will enable project success to be achieved (Chinyio and Akintoye, 2008). For instance, while some stakeholders can be communicated to using letters/flyers about project decision others must be contacted directly through meetings/workshops or project website to get their inputs

1
2
3
4
5
6
7 292 about the project depending on their classification in the project. Therefore, this construct is
8
9 293 indicated by the project management’s ability to involve relevant stakeholders in refining
10
11 294 project mission whenever necessary; formulate appropriate strategies to manage/engage
12
13 295 different stakeholders; keep and promote positive relationships among the stakeholders;
14
15 296 communicating with stakeholders properly and frequently with feedback mechanisms; and
16
17 297 considering all social responsibility issues surrounding the project.
18
19 298 Under this construct, the following hypotheses are stated:
20
21
22 299 *Hypothesis 9:* Effective stakeholder engagement/empowerment (SE) influences the
23
24 300 impact of stakeholder management on construction project success (PS).
25
26 301 *Hypothesis 10:* Obtaining adequate information on stakeholder characteristics and
27
28 302 project characteristics (SCPC) enables effective stakeholder engagement/empowerment (SE).
29
30
31 303 <Table 2>
32
33 304 <Figure 1>
34
35
36 305 Based on the hypotheses stated under the four constructs of CSFs for stakeholder
37
38 306 management in construction projects, adequately obtaining information on stakeholder
39
40 307 characteristics and project characteristics (SCPC); carrying out informed stakeholder analysis
41
42 308 (SA); understanding stakeholder dynamics (SD); and effective stakeholder
43
44 309 engagement/empowerment (SE),, a structural model is developed (portrayed in Figure 2) to
45
46 310 further investigate the interrelationships among the critical success factors for stakeholder
47
48 311 management in construction and how they relate to project success:
49
50 312 <Figure 2>
51
52
53
54
55
56
57
58
59
60

RESEARCH METHODS ADOPTED TO TEST THE CONCEPTUAL MEASUREMENT AND STRUCTURAL MODELS

Data collection and screening

A quantitative approach was adopted to empirically test the conceptual model of the interrelations among CSFs for stakeholder management in construction. A questionnaire was designed to investigate 23 CSFs grouped under four latent variables (constructs) to elicit responses from construction professionals within United Kingdom. Professionals in architecture, construction management, quantity surveying, engineering, facility management, including clients' representatives and designers etc with at least five years of relevant professional experience working on large construction projects with multiple stakeholder issues were targeted to participate in the survey. The survey respondents were asked to rate their agreement with the CSFs as indicators of stakeholder management decisions/actions and their influence on stakeholder management and project success based on a five point Likert scale in which 1 = strongly disagree and 5 = strongly agree. The questionnaire also gathered background information of the respondents in order to ensure that they have the required background and years of professional experience to take part in this survey before their responses are used for analyses. A minimum of 5 years relevant professional experience was set for the respondents to ensure they have participated in some projects up to completion so that they can have practical knowledge of stakeholder management issues.

Stratified random sampling was used to select respondents from construction professionals practicing in the UK the entire population of which could not be ascertained. The respondents were selected through the website/company profiles of construction organisations delivering construction services. According to Saunders, et al. (2009) if the size of population is not known the following formula can be used to determine the sample size

1
2
3
4
5
6
7 338 | for survey research: Sample size = [(minimum sample size required × 100) ÷ Average
8 339 | percentage response rate expected]. For the purpose of sampling analysis, a minimum of 50
9
10 340 | responses was required to achieve the objectives of the current study (Iacobucci, 2010).
11
12 341 | Using an estimated response rate of 25% based on the average response rate obtainable in
13
14 342 | similar research in construction management, the sample population size for the current study
15
16 343 | was determined as follows: [(50 × 100) ÷ 25] = 200 (Saunders, et al. 2009). The survey link
17
18 344 | was therefore sent to 200 professionals practicing within the United Kingdom. After two
19
20 345 | reminders (at one month’s interval each) a total of 74 responses were received representing
21
22 346 | 37% of the total number of respondents to whom the link to the survey was emailed. Out of
23
24 347 | the 74 responses received, 13 were rejected for having less than 5 years of professional
25
26 348 | experience in construction and/or for incomplete responses. 61 responses (30.5% of
27
28 349 | respondents contacted) were found suitable and accepted for analysis;

29
30 350 | **Data Analysis**

31
32 351 | Several statistical tools have been considered when selecting the appropriate analysis
33
34 352 | tool for the current study. To examine the groupings of the critical success factors for
35
36 353 | stakeholder management in construction, confirmatory factor analysis (also known as the
37
38 354 | measurement component of SEM) can be used. Whereas, to investigate the interrelationships
39
40 355 | among the CSFs through their constructs; different forms of regression analysis can be used
41
42 356 | in a step by step fashion. However, the hypothesised models in the current study require the
43
44 357 | interrelationships to be explored simultaneously in a holistic manner so that errors of
45
46 358 | measurement can be adequately taken into account. To achieve this objective, structural
47
48 359 | equation modelling (SEM) was considered the most appropriate. SEM was chosen over other
49
50 360 | multivariate statistical analysis methods due to its ability for the simultaneous examination of
51
52 361 | relationships among a number of dependent (latent) and independent (observed) variables
53
54 362 | (Hair *et al.*, 1998). Another reason for choosing SEM was its ability to take into account the

measurement errors inherent in subjective operational measurement and to define and explain the entire set of relationships in the hypothesised model (Byrne, 2010).

The development of SEM usually goes through some basic stages (Hair *et al.*, 1998) which include:

1. Identify and define (operationally) the model components (which include latent variables, measured variables and any other variables) based on theory.
2. Set up a hypothetical model (model specification) which sometimes may involve setting up more than one model (competing models) depending on the theoretical bases and aim of the research;
3. Assess the validity of the model using data collected based on the operationalised components (variables) of the model by evaluating model estimates and goodness of fit indices; and
4. Identify potential model changes and modify the model with theoretical justification.

The first two stages were achieved using literature review to identify the model components and set up hypothetical models (including measurement and structural models) and the last two stages were achieved during the data analysis stages of the study presented in this paper. In this study, no alternative models were developed as the aim was to investigate the interrelationships among CSF for stakeholder management in construction and how they are related to project success rather than comparing candidate theories and choose from. Competing models are used only when there are well established alternative/competing theories to be tested in the study (Kline, 2005). The conceptual structural model in this study includes all possible hypotheses on the relationships between the constructs and tests the validity of each hypothesis on a single model.

1
2
3
4
5
6
7 386 SEM analysis comprise of two components; the measurement component and the
8
9 387 structural components. While the measurement component enables analysis of relationships
10
11 388 between the latent variables (constructs) and their indicators (observed variables); the
12
13 389 structural component is used to analyse interrelationships among the latent variables. The
14
15 390 measurement model also takes into account the measurement errors associated with the
16
17 391 indicators which are measured operationally.

18
19 392 There is no consensus on the acceptable thresholds for sample sizes among
20
21 393 researchers that used SEM. One group of researchers recommend large sample sizes (from
22
23 394 100 to 400) whereas construction management researchers (for example; Doloi *et al.*, 2012;
24
25 395 Doloi, 2009; Erikson and Pesamaa, 2007; Ozorhon *et al.*, 2007; Islam and Faniran, 2005,
26
27 396 Mohammed, 2000) have used smaller sample sizes, giving different reasons for doing so. The
28
29 397 61 responses in the current study having been collected from well experienced respondents
30
31 398 with relevant professional backgrounds working on large projects with demanding
32
33 399 stakeholder issues to whom the research objectives were clearly explained are considered
34
35 400 reliable. Furthermore, the spread across construction professionals among the respondents,
36
37 401 adds to the reliability of the data for investigating critical success factors for stakeholder
38
39 402 management in construction. Table 3 presents the respondents' profiles in terms of their years
40
41 403 of professional experience and professional field of practice with all of them, having relevant
42
43 404 experience of at least 5 years and over 78% of them having 10 years and above experience.

44 405 Moreover, all the targeted respondents are known to have worked on projects with multi
45
46 406 parties and had to collaborate or engage with all or most of the parties. It was ensured during
47
48 407 sampling that the respondents with the professional fields of architecture, construction
49
50 408 management and engineering; include clients' representatives and designers. Given the
51
52 409 inherent difficulty to collect questionnaire data in construction management research and
53
54 410 coupled with the characteristics sought in the targeted respondents which limit the number of

eligible respondents, 61 is a good sample size for this study. If the model to be tested using SEM is not overly complex and source of data is very reliable, sample size of 50 can be enough (Iacobucci, 2009).

<Table 3>

Preliminary Analysis for Consistency Checks

Preliminary (consistency) analyses including mean ratings of the CSFs, un-rotated principal component factor analysis and standardised Cronbach's alpha coefficient were performed using IBM SPSS 20. The mean ratings of the CSFs were obtained to check for acceptance of the CSFs by the respondents; un-rotated principal component factor analysis was performed to check for commonality within the data set; and standardised Cronbach's alpha coefficient was used to check for reliability of measurement within the data set. Finally, structural equation modelling with IBM AMOS 20 software was used to test the hypothesised measurement model of the interrelations among the CSFs and their latent variables. The results are presented in the subsequent sections.

ACCEPTANCE, COMMONALITY AND RELIABILITY TESTS RESULTS

It was necessary to carry out consistency tests to make sure that there are no issues of consistency associated with the data set. These tests include the mean ratings and ranking of all CSFs by the survey respondents to ascertain the acceptance of the CSFs by the respondents; un-rotated principal component analysis to check for commonality; and Cronbach's alpha coefficient test to check for reliability of the measured variables scale (Hair *et al.*, 2008). All of these tests were done using IBM SPSS 20 software.

The result of mean rating presented in Table 4 reveals high level of agreement that the CSFs are important for stakeholder management in construction projects. The factor with the

1
2
3
4
5
6
7 434 highest rating by all respondents is “involving relevant project stakeholders at the inception
8
9 435 stage and whenever necessary to refine project mission” (SE1) with mean rating of 4.43 and
10
11 436 the factor with the lowest rating is “ensuring the use of flexible project organisation”
12
13 437 (SCPC4) with mean rating of 3.85.

14
15 438 The result of un-rotated principal component analysis revealed the existence of more
16
17 439 than one factor (up to 6 possible factors) as shown in Appendix A, indicating that
18
19 440 commonality is not an issue within the data. If the results of un-rotated principal component
20
21 441 factor analysis reveal the existence of only one factor, then it suggests that commonality is an
22
23 442 issue meaning the factors in the data set are likely to fall into the same group (Schriesheim,
24
25 443 1979).

26
27 444 Standardised Cronbach’s alpha coefficient of 0.907 was obtained for the measured
28
29 445 variables indicating high reliability. Cronbach’s alpha values should be at least 0.70 with
30
31 446 values closer to 1.0, indicating better reliability (Nunnally and Bernstein, 1994; Hair *et al.*,
32
33 447 2008). Having confirmed the acceptance of all the CSFs, absence of commonality and
34
35 448 reliability, the measurement model was then tested.

36
37
38 449 <Table 4>

39
40
41 450 **RESULTS OF MEASUREMENT MODEL OF CSFS FOR STAKEHOLDER**
42
43 451 **MANAGEMENT IN CONSTRUCTION**

44
45 452 IBM SPSS AMOS 20 software was used to empirically test the hypothetical model of
46
47 453 critical success factors (CSFs) for stakeholder management in construction. To achieve this,
48
49 454 the measurement model component of structural equation modelling (SEM) was used to
50
51 455 investigate the appropriateness and strength of the relationships between the observed and

latent variables as well as to measure if there are any, correlations/co-variances among the four latent variables.

Using confirmatory factor analysis (CFA) also known as “measurement model”, the assessment of fit between the data collected and the theoretically conceptual model (Figure 1) of the relationships between observed and latent variables was done. It is important to note that the latent variables in the hypothetical model include: stakeholder characteristics and project characteristics (SCPC); stakeholder analysis (SA); stakeholder dynamics (SD); and stakeholder engagement/empowerment (SE); and their indicators (measured variables) are the CSFs presented in Table 1.

SEM uses goodness-of-fit (GOF) indices shown in Table 5 from the output obtained in AMOS in order to assess how well the hypothesised model fits the data set. The GOF indices used in this study include the root mean square residual (RMR), comparative fit index (CFI), incremental fit index (IFI), Tucker-Lewis index (TLI), goodness of fit index (GFI), ratio of minimum discrepancy to the degrees of freedom (CMIN/DF) and root mean square error of approximation (Anderson and Gerbing, 1984; Kline, 2004; Iacobucci, 2010). The RMR computes the residual differences between the data set and model prediction and take the square root of the result. It ranges from 0 – 1 with smaller values indicating better fit. The CFI compares the fit of a baseline model to the data with the fit of the hypothesised model to then same data. It also ranges from 0 – 1 but with larger values indicating better fit. IFI is the ratio of the difference between the discrepancy and degrees of freedom of the hypothesised model and that of the baseline model. It also ranges from 0 – 1 with larger values showing better fit. The TLI compares the discrepancy and degrees of freedom for the hypothesised model with those of the baseline model. It also ranges from 0 – 1 with larger values indicating better fit. The GFI is a test if the maximum likelihood estimate of the hypothesised model fit to the data set. It also ranges from 0 – 1 and higher values indicate better fit. The

1
2
3
4
5
6
7 481 CMIN/DF adjusts the chi-square by computing the ration of the minimum discrepancy to
8
9 482 degrees of freedom. It ranges from 1- 2 with vales closer to 1 indicating closer fit.
10
11 483 After analysing the hypothesised measurement model, the path coefficients and the
12
13 484 GOF indices revealed the need to refine/modify the measurement model. Three main
14
15 485 considerations are used to modify models in SEM (Kline, 2005). These include: looking for
16
17 486 and eliminating paths with very low factor loadings; removing variables indicated by the
18
19 487 modification indices as having multi-co-linearity; and removing observed variables with very
20
21 488 high values in the standardised residual correlation matrix. Additionally, model
22
23 489 refinement/modification should lead to the selection of a fitting model which satisfies not
24
25 490 only the GOF measures but also falls within and satisfies the theoretical expectation
26
27 491 (Molenaar, *et al.*, 2000; Byrne, 2010). After going through the refinement/modification steps,
28
29 492 seven observed variables were dropped from the hypothesised measurement model for
30
31 493 showing signs of multi-co-linearity and having many high standardised residual correlations
32
33 494 above 0.4: three from SCPC (SCPC1, SCPC4, and SCPC5); three from SD (SD1, SD6, and
34
35 495 SD7) and one from SE (SE4). Furthermore, three observed variables (SA1, SA2, and SE1)
36
37 496 have been relocated to another construct and all the correlations among the latent variables
38
39 497 were retained (see Table 6). Since the CSFs excluded from the measurement model have
40
41 498 been strongly accepted by the respondents based on their mean ratings presented in Table 4;
42
43 499 they have been compared with and realigned into other factors that have been retained in the
44
45 500 final measurement model. The reason is to avoid losing too much of the CSFs and care was
46
47 501 taken to ensure that the final CSFs constituting the measured variables in the best fitting
48
49 502 model are still consistent with the extant theoretical postulations. This lead to the merging
50
51 503 (realignment) of CSFs presented in Table 7 based on which the final measurement and
52
53 504 structural models were analysed. The resultant best fitting measurement model is portrayed in
54
55 505 Figure 3 as further refinement/modification failed to improve the model fit. The GOF indices
56
57
58
59
60

for both the conceptual measurement model and the fitting measurement model are presented in Table 5.

<Table 5>

<Figure 3>

The strength with which the observed variables measure the latent variables in the best fit measurement model, is indicated by their standardised path coefficients (also known as factor loading). Table 6 shows the path coefficients of the influence of the observed variables on the latent variables. Since the standardised path coefficients range from 0.54 to 0.89, it is indicated that the retained observed variables significantly measure the latent variables. Moreover, all the path coefficients are positive and statistically significant at level $P < 0.05$, therefore, they are supported. Values of factor loading equal to or greater than 0.40 with significant P value < 0.05 indicate strong measurement with values closer to 1 indicating stronger measurement (Li *et al.*, 2005; Akson and Hadikusumo, 2008). This suggests that the latent variables are valid groupings of the CSFs for stakeholder management in construction projects.

<Table 6>

<Table 7>

Similarly, the strengths of the correlations and covariant relationships among the latent variables are shown in Table 8 indicating that the latent variables strongly affect one another positively with the smallest value of correlation being 0.579 (between SD and SE) which is still above the minimum threshold of 0.5. Furthermore, all the correlations are statistically significant at level $P < 0.05$ and the covariance estimates are all below the maximum threshold of 0.3. The standard errors (S.E.) do not present with any outliers (i.e.

1
2
3
4
5
6
7 529 any extremely large or small values) same as the critical ratios (C.R.). Therefore, all the
8
9 530 hypothesised correlations among the latent variables are supported and the specific
10
11 531 interrelationships among them can be investigated in a structural component of SEM.
12
13 532 <Table 8>

16
17 533 **RESULTS OF STRUCTURAL MODEL AND HYPOTHESES TESTING**

18
19 534 Figure 4 presents the final structural equation model of CSFs for stakeholder
20
21 535 management in construction projects with standardised path coefficients on the structural
22
23 536 paths of the supported hypothesised relationships shown in Figure 2. The standardised path
24
25 537 coefficients of the hypothesised relationships were tested using critical ratios, standard errors
26
27 538 and their level of statistical significance to ascertain whether the hypotheses are supported by
28
29 539 the data set or not (see Table 9).
30
31 540 <Figure 4>

32
33
34 541 As presented in Table 9, the standard errors (S.E.) do not present with any extremely
35
36 542 high or low values except for that of H4. The critical ratios (C.R.) for H1, H3, H4 and H6 are
37
38 543 extremely low and a further look at the results presented in Table 9 reveal that only four hy-
39
40 544 pothesised relationships are supported at the statistical significance level of $P < 0.05$. The rela-
41
42 545 tionship path between stakeholder characteristics and project characteristics (SCPC) and
43
44 546 stakeholder dynamism (SD) with insignificant P value of 0.322 and low path coefficient of
45
46 547 0.255 does not support Hypothesis 3. Similarly the paths between stakeholder analysis (SA)
47
48 548 and project success (PS) with insignificant P value of 0.721 and a negative low path coeffi-
49
50 549 cient of -0.125; stakeholder dynamism (SD) and project success (PS) with insignificant P
51
52 550 value of 0.902 and a low path coefficient of 0.041; stakeholder characteristics and project
53
54 551 characteristics (SCPC0 and project success (PS) with insignificant P value 0.968 and low

path coefficient of 0.012 failed to support Hypotheses 4, 6, 1 respectively. Conversely, the relationship path between stakeholder characteristics and project characteristics (SCPC) and stakeholder analysis (SA) with P value of 0.002 and path coefficient of 0.772 strongly supports Hypothesis 2. Other hypotheses supported by the results presented in Table 9 include Hypotheses 7, 8 and 9. They are supported by the paths between stakeholder analysis (SA) and stakeholder dynamism (SD) with significant P value of 0.025 and acceptable path coefficient of 0.608; stakeholder dynamism (SD) and stakeholder engagement/empowerment (SE) with very significant P value and acceptable path coefficient of 0.634; and stakeholder engagement/empowerment (SE) and project (PS) with significant P value of 0.008 and acceptable path coefficient of 0.695; respectively. Table 10 presents the GOF measures for the conceptual and best fitting structural models of critical success factors for stakeholder management in construction. Figure 4 indicates improvement in the strengths of the supported hypothesis after deleting the hypotheses not supported as shown in Table 9.

<Table 9>

<Table 10>

DISCUSSION OF FINDINGS

This study investigated the interrelationships among the CSFs for stakeholder management in construction projects based on four latent variables drawn from previous research. The results indicate the existence of statistically significant relationships between the measured (CSFs) and latent variables and among the latent variables (SCPC, SA, SD and SE).

The findings based on the measurement model indicate that SCPC4 “Ensuring the use of flexible project organisation” has the least mean rating 3.85 which is still way above the

1
2
3
4
5
6
7 575 acceptable rating for a five-point Likert scale being 3.5. This connotes that the survey
8
9 576 respondents considered all the 23 CSFs as vital for the success of stakeholder management in
10
11 577 construction which is partly in line with the findings of Yang *et al.*, (2009) except for the
12
13 578 additional CSFs. Furthermore, Yang *et al.* (2009) found that SE5 (Considering corporate
14
15 579 social responsibilities (paying attention to Economic, legal, environmental, and ethical
16
17 580 issues)) was the most important CSF and could not be grouped under any of the constructs
18
19 581 and identified it as the precondition factor of stakeholder management in construction
20
21 582 projects. However, the findings in the current study grouped SE5 under stakeholder
22
23 583 engagement (SE) with a factor loading of 0.68. Additionally, the most important CSF in the
24
25 584 current study is SE1 (Involving relevant project stakeholders at the inception stage and
26
27 585 whenever necessary to refine project mission) which was initially hypothesised to be under
28
29 586 the construct stakeholder engagement/empowerment (SE) but the result of the measurement
30
31 587 model analysis moved it to the construct stakeholder characteristics and project
32
33 588 characteristics (SCPC). As reported in the preceding section, the results of the “measurement
34
35 589 model” excluded 7 CSFs from the best fitting measurement model including SCPC1, SCPC4,
36
37 590 SCPC5, SD1, SD6, SD7 and SE4 which were deleted during model modification (please see
38
39 591 Table 4 for their full meanings).

40
41 592 The strong correlation estimates presented in Table 8 pointed to the existence of some
42
43 593 interrelationships direct or indirect among the constructs of CSFs for stakeholder
44
45 594 management in construction (SCPC, SA, SD and SE). When the hypothesized relationships
46
47 595 were tested, the final structural model suggested that only one of the constructs, stakeholder
48
49 596 engagement/empowerment has a direct positive impact on project success. The results [\(See](#)
50
51 597 [Figure 4 and Table 9\)](#) indicated that the other three constructs (SCPC, SA and SD) can not
52
53 598 directly influence project success (PS) but they influence project success indirectly by their
54
55 599 collective interactions through stakeholder engagement/empowerment (SE) as follows:

56
57
58
59
60

- Stakeholder characteristics and project characteristics (SCPC) influence stakeholder analysis (SA) with a very high path coefficient of 0.81 and a significant P value of 0.026.
- Stakeholder analysis (SA) in turn influences the understanding of stakeholder dynamism (SD) with an equally high path coefficient of 0.83 and a significant P value of 0.002.
- The understanding of stakeholder dynamism (SD) will enable stakeholder engagement/empowerment (SE) with an acceptable path coefficient of 0.62 and a very significant p value.
- Stakeholder engagement/empowerment (SE) influences project success (PS) with an acceptable path coefficient of 0.65 and a very significant P value.

The finding that stakeholder analysis (SA) can not directly impact/influence project success (PS) is a shift from the view within the construction based stakeholder management literature that stakeholder analysis can lead to project success (Jepsen and Eskerod, 2009; Olander and Landin, 2005). However, stakeholder engagement/empowerment (SE) being the only construct found to directly influence project success (PS) depends on the understanding of stakeholder dynamism (SD) which also depends very strongly on the results of stakeholder analysis (SA). The finding that understanding stakeholder dynamism (SD) depends on the results of stakeholder analysis (SA) is in agreement with the position of Aaltonen *et al.* (2008). Moreover, the lack of support for the H3 (Obtaining adequate information on stakeholder characteristics and project characteristics – SCPC enables the understanding of stakeholder dynamism – SD) can be considered counter intuitive. Furthermore, the findings suggest that obtaining information on project characteristics and stakeholder characteristics (SCPC) is a major precondition step in the process of stakeholder management. This finding is in line with the opinion canvassed by a faction of the extant literature (Mitchell *et al.*,

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15

6251997; Chinyio and Akintoye, 2008) and disagrees with the position of Yang *et al.* (2009) that

626the precondition factor for stakeholder management in construction projects is “considering

627corporate social responsibilities” which by the findings of the current study is an indicator of

628stakeholder engagement/empowerment (SE).

16
17

629**CONCLUSIONS**

18
19
20
21
22
23
24
25
26
27
28
29
30
31

630The aim of this study was to enhance the knowledge on stakeholder management in

631construction and improve the understanding of the critical success factors of stakeholder

632management and the interrelations among them. In order to achieve this aim, a conceptual

633measurement model was developed based on the analysis of literature review findings. The fit

634between the extant theoretical standing and the survey data was examined and after an

635iterative statistical process the final structural model for critical success factors of stakeholder

636management was developed and accepted.

32
33
34
35
36
37
38
39
40
41
42

637

638Effects of stakeholder analysis, stakeholder characteristics and project characteristics,

639stakeholder engagement and stakeholder dynamics on the stakeholder management and on

640project success were investigated. The reliability of each construct and the overall model is

641highly satisfactory as all goodness of fit indices were very good.

43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

642The findings indicated that that all stakeholder management decisions made in the

643four distinct constructs (obtaining information on project characteristics and stakeholder

644characteristics; undertaking stakeholder analysis; understanding stakeholder dynamism; and

645stakeholder engagement/empowerment) affect each other directly or indirectly as follows:

- The ability of the project management team to clearly obtain adequate information on stakeholder characteristics and project characteristics will influence and aid their ability to carry out stakeholder analysis.
- Understanding stakeholder dynamism depends on the results of stakeholder analysis.
- Decisions on how to effectively engage/empower stakeholders during construction projects relies on the good understanding of stakeholder dynamism.
- Effective stakeholder engagement/empowerment will facilitate project success

These relationships indicated that obtaining information about project characteristics and stakeholder characteristics (SCPC) is the precondition factor (construct) to be able to carry out effective stakeholder management in construction. Failure to adequately and holistically address the critical success factors for stakeholder management in construction projects will prevent stakeholder management efforts from achieving the desired results-project success.

The main contribution of this study to existing knowledge is an empirical evidence of the interrelationships among the CSFs for stakeholder management in construction through their latent variables which is portrayed in the best fitting structural model (Figure 4) showing the relationships between the constructs of CSFs for stakeholder management and project success. This should serve as a guide to construction project management team or responsible professionals for successfully undertaking stakeholder management in construction projects.

From the result presented in Table 4, all the 23 CSFs for stakeholder Management in construction projects should be given adequate considerations. None the less, the five most important CSFs are:

1. SE1 – Involving relevant project stakeholders at the inception stage and whenever necessary to refine project mission:

Formatted: Font: Times New Roman, 12 pt

Formatted: List Paragraph, Numbered + Level: 1 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0.75" + Indent at: 1"

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695

2. SCPC5 – Identifying and understanding stakeholders’ areas of interests in the project;

3. SE4 – Communication with stakeholders properly and frequently;

4. SD6 – Managing how project decisions affect stakeholders; and

5. SD1 – Resolving conflicts among stakeholders effectively.

Based on the findings portrayed in Figure 4 and highlighted in the conclusion, the first thing to do in order to be successful in stakeholder management, is to indentify Stakeholder Characteristics and Project Characteristics (SCPC) following which Stakeholder Analysis (SA) is performed the results of which will inform the project management team of the project’s Stakeholder Dynamism (SD) based on which appropriate Stakeholder Engagement/Empowerment techniques (SE) are Decided. Therefore, the practical steps for successful stakeholder management in construction project are to follow the following sequence: Indentify Stakeholder Characteristics and Project Characteristics (SCPC) – Carry out Stakeholder Analysis (SA) – Understand Stakeholder Dynamism (SD) – Decide Stakeholder Engagement/Empowerment techniques (SE). Likewise this should serve as a guide for further research on stakeholder management processes.

The main limitation of this study is that only the opinion of the key internal stakeholders was considered. Further research should therefore take into account the opinions of a wider range of stakeholders including external stakeholders. Furthermore, a larger sample size should be targeted in similar future studies. Moreover, ~~T~~the research reported in this paper was carried out in the UK as discussed earlier under the research methods section; hence the findings may have portrayed the UK construction professionals’ opinion. However, the theoretical principles on which the research was based are general and similar research could be replicated in different countries whose construction procurement processes and industries are structured like those of the UK or otherwise. Furthermore, the sequential steps

<http://mc.manuscriptcentral.com/ecaam>

of the process of stakeholder management portrayed in Figure 4 can be tested on real life projects.

REFERENCES

- Aaltonen, K., Jaakko, K. And Tuomas, O. (2008). Stakeholder salience in global project, *International Journal of Project Management*, 26, 509-516.
- Akintoye, A., Hardcastle, C., Beck, M., Chinyio, E., and Asenova, D. (2003). Achieving best value in private finance initiative project procurement, *Construction Management and Economics*, 21(5), 461 – 470.
- Aksorn, T.; Hadikusumo, B. H. W. (2008). Critical success factors influencing safety program performance in Thai construction projects, *Safety Science* 46: 709–727. Doi:10.1016/j.ssci.2007.06.006
- Atkin, B. and Skitmore, M. (2008) Editorial: Stakeholder management in construction, *Construction Management and Economics*, 26: 6, 549 – 552.
- Black, K., (1995). Causes of project failure: a survey of professional engineers. *PM Network*, November; 21-24.
- Bourne, L. (2005) Project relationship management and the stakeholder circle, Doctoral thesis, *Graduate School of Business, Melbourne*, RMIT University.
- Bourne, L. and Walker, D.H.T. (2005). Visualising and mapping stakeholder influence. *Management Decision*, 43(5), 649–60.
- Byrne, B. M. (2010). *Structural Equation Modelling with AMOS: Basic Concepts, Applications and Programming*, (2nd ed.), Routledge, Taylor and Francis Group, New York.

1
2
3
4
5
6
7 718 Cheeks, J. R. (2003). Multistep disputes resolution in design and construction industry.
8
9 719 *Journal of Professional Issues in Engineering Education and Practice*, ASCE,
10
11 720 129(2), 84-91.
12
13 721 Chinyio, E. A. and Akintoye, A. (2008). Practical approaches for engaging stakeholders:
14
15 722 findings from the UK, *Construction Management and Economics*, 26: 6, 591-599.
16
17 723 Cleland, D.I., 1999. *Project Management Strategic Design and Implementation*. McGraw-
18
19 724 Hill, New York.
20
21 725 Doloi, H., Sawhney, A. and Iyer, K. C. (2012a). Structural equation model for investigating
22
23 726 factors affecting delay in Indian construction projects. *Construction Management and*
24
25 727 *Economics*, DOI:10.1080/01446193.2012.717705, 1-16.
26
27 728 Egan, J., (1998). Rethinking construction: report of the construction task force on the scope
28
29 729 for improving the quality and efficiency of UK construction, *Department of the*
30
31 730 *Environment, Transport and the Region*, London.
32
33 731 Eriksson, P.E. and Pesamaa, O. (2007). Modelling procurement effects on cooperation.
34
35 732 *Construction Management and Economics*, 25, 893–901.
36
37 733 Hair, J.F., Anderson, R.E., Tatham, R.L. and Black, W.C. (2008). *Multivariate Data*
38
39 734 *Analysis*, (7th ed.). Prentice Hall Publisher, Upper Saddle River, New Jersey.
40
41 735 Ibrahim, R., Nissen, M., (2003). Emerging Technology to Model Dynamic Knowledge
42
43 736 Creation and Flow among Construction Industry Stakeholders during the Critical
44
45 737 Feasibility-Entitlements Phase. *Proceedings of The American Society of Civil Engineers*
46
47 738 *(ASCE) 4th Joint Symposium on IT in Civil Engineering*. ASCE, Nashville, TN, pp. 1–14.
48
49 739 Nov. 15-16.
50
51 740 Iacobucci, D. (2010). Structural equations modelling: Fit indices, sample size, and advanced
52
53 741 topics. *Journal of Consumer Psychology*, 20, 90-98.
54
55
56
57
58
59
60

- Islam, M.D.M. and Faniran, O.O. (2005). Structural equation model of project planning effectiveness, *Construction Management and Economics*, 23, 215–23.
- Jepsen, A. L. And Eskerod, P. (2009). Stakeholder analysis in projects: challenges in using current guidelines in the real world, *International Journal of Project Management* 27, 335 – 345.
- Jergeas, G.E., Williamson, E., Skulmoski, G.J., Thomas, J.L., (2000). Stakeholder management on construction projects. *AACE International Transactions* 12, 1–5.
- Karlsen, J. T. (2002). Project stakeholder management, *Engineering Management Journal*, 14: 4, 19-24.
- Kline, R.B. (2005). *Principles and Practice of Structural Equation Modelling: Methodology in the Social Sciences*. Guilford Press, New York.
- Leung, M. and Olomolaiye, P. (2010). Risk and construction stakeholder management. In: Chinyio, E. and Olomolaiye, P. (Eds.) *Construction Stakeholder Management*, John Wiley & Sons Ltd, United Kingdom, Pg 75 – 98.
- Li, B.; Akintoye, A.; Edwards, P. J.; Hardcastle, C. (2005). Critical success factors for PPP/PFI projects in the UK construction industry, *Construction Management and Economics* 23: 459–471.
- Li, T. H. Y., Ng, T. S. and Skitmore, M. (2012). Conflict or consensus: An investigation of stakeholder concerns during the participation process of major infrastructure and construction projects in Hong Kong, *Habitat International*, 36, 333 – 342.
- Mathur, V. N., Price, A. D. F. And Austin, S. (2008). Conceptualizing stakeholder engagement in the context of sustainability and its assessment, *Construction Management and Economics*, 26: 6, 601-609.

1
2
3
4
5
6
7 765 Mitchel, R. K., Agle, B. R. And Wood, D. J. (1997). Toward a theory of stakeholder
8 766 identification and salience: defining the principle of who and what really counts,
9 767 *Academy management review*, vol 22 no 4.
10
11
12 768 Molenaar, K., Washington, S. and Diekmann, J. (2000). Structural equation model of
13
14 769 construction contract dispute potential. *J. Constr. Eng. Manage.*, 126 (4), 268–277.
15
16 770 Molwus, J. J., Erdogan, B., and Ogunlana, S. O. (2013). Critical success factors for
17
18 771 stakeholder management and project success in construction projects. *11th International*
19
20 772 *Post Graduate Research Conference (IPGRC)*, 8th –10th April, Media city, Manchester,
21
22 773 University of Salford, 758 – 767.
23
24 774 Nash, S., Chinyio, E., Gameson, R. and Suresh, S. (2010). The dynamism of stakeholders’
25
26 775 power in construction projects. In: *Egbu, C. (Ed) procs 26th Annual ARCOM conference*,
27
28 776 6 – 8 September, Leeds, UK, Association of Researchers in Construction Management,
29
30 777 471 – 480.
31
32 778 Nunnally, J.C. and Bernstein, I.H. (1994) *Psychometric Theory*, McGraw-Hill, New York.
33
34 779 Olander, S. and Landin, A. (2005). Evaluation of Stakeholder influence in the
35
36 780 implementation of construction projects, *International Journal of Project Management*,
37
38 781 23, pp 321-328.
39
40 782 Olander, S. and Landin, A. (2008). A comparative studies of factors affecting the external
41
42 783 stakeholder management process, *Construction Management and Economics*, 26(6),
43
44 784 553.doi:10.1080/01446190701821810
45
46 785 Pajunen, K. (2006). Stakeholder influences in organisational survival, *Journal of*
47
48 786 *Management Studies*, 43(6), 1261-88.
49
50 787 Pallant, J., (2007). *Survival manual: A step by step guide to data analysis using SPSS for*
51
52 788 *windows*, 3rd Edition, *Open University press*, McGraw-Hill, Uk.
53
54
55
56
57
58
59
60

- 789 Rockart, J.F., (1979). Chief executives define their own data needs. *Harvard Business review*;
790 57(2): 81–93.
- 791 Saunders, M., Lewis P. and Thornhill, A. (2009). *Research Methods for Business Students*.
792 Financial Times Prentice Hall Inc., London.
- 793 Schriesheim, C.A. (1979). The similarity of individual directed and group directed leader
794 behavior descriptions. *Academy of Management Journal*, 22, 345–55.
- 795 Takim, R. (2009). The Management of Stakeholders' Needs and Expectations in the
796 Development of Construction Projects in Malaysia, *Modern Applied Science*, vol. 3 No. 5
797 pp 167-175, www.ccsenet.org/journal.html, available 17/11/2010.
- 798 Winch, G. M., (2010). Managing Construction projects: an information processing approach,
799 2nd Edition, *Wiley-Blackwell*, West Sussex, UK.
- 800 Yang, J., *et al.* (2009). Exploring critical success factors for stakeholder management in
801 construction projects, *Journal of Civil Engineering and Management*, 15: 4, 337-348.
- 802 Yang, R. J. (2014). An Investigation in Stakeholder Analysis in Urban Development Projects:
803 Empirical or Rationalistic Perspectives, *International journal of Project Management*,
804 32(5), 838-849.
- 805 Yang, R. J. and Shen, G. Q. P., (2014). Framework for stakeholder management in
806 construction projects, *Journal of Management in Engineering*, DOI:
807 10.1061/(ASCE)ME.1943-5479.0000285.

Formatted: Reference, Left, Indent: Left: 0",
First line: 0"

809 List of Tables

- 810 Table 1 List of critical success factors (CSFs) for stakeholder management in construction
- 811 Table 2 Constructs and indicators of conceptual measurement model of CSFs for stakeholder
812 management in construction
- 813 Table 3 Respondents' profiles

1
2
3
4
5
6
7 814 Table 4 Mean rating and ranking of Critical Success Factors for Stakeholder Management
8
9 815 Table 5 Result of GOF measures for both Conceptual and best fitting measurement models of
10 816 the CSFs for stakeholder management in construction
11
12 817 Table 6 Standardised path coefficients of observed variables' loading on latent variables
13
14 818 Table 7 Realigned critical success factors for stakeholder management in construction
15
16 819 projects
17
18 820 Table 8 Standardised correlation and covariance coefficients of the best fitting measurement
19
20 821 model of CSFs for stakeholder management in construction
21
22 822 Table 9 Standardised path coefficients of the conceptual structural model of the interrelations
23
24 823 among CSFs for stakeholder management in construction
25
26 824 Table 10 Result of GOF measures for both Conceptual and best fitting structural models
27
28 825 **Table 1 List of critical success factors (CSFs) for stakeholder management in**
29
30 826 **construction**

S/N	CSF	Source
1	Clearly formulating the project mission	Jerges <i>et al.</i> , (2000); Akintoye <i>et al.</i> (2003) Thomson <i>et al.</i> , (2003); Chinyio and Akintoye, (2008)
2	Ensuring the use of a favourable procurement method	Atkin and Skitmore, (2008); Olander and Landin, (2008); Rwelamila, (2010)
3	Carefully identifying and listing the project stakeholders	Mathur <i>et al.</i> , (2008); Jepsen and Eskerod, (2009)
4	Ensuring flexible project organisation	Olander and Landin, (2008); Chinyio and Akintoye, (2008);
5	Identifying and understanding stakeholders' areas of interests in the project	Jepsen and Eskerod, (2009); Olander and Landin, (2008); Yang <i>et al.</i> , (2009)
6	Determining and assessing the power (capacity to influence the actions of other stakeholders); urgency (degree to which stakeholders' claims requires immediate attention);	Mitchell <i>et al.</i> , (1997); Yang <i>et al.</i> , (2009)

S/N	CSF	Source
	legitimacy (perceived validity of claims); and proximity (level of association or closeness with the project) of stakeholders	
7	Appropriately classifying stakeholders according to their attributes/characteristics	Karlsen, (2002); Mitchell <i>et al.</i> , (1997)
8	Predicting and mapping stakeholders' behaviours (supportive, opposition, neutral etc)	Yang <i>et al.</i> , (2009)
9	Predicting stakeholders' potential influence on each other	Pajunen, (2006); Jepsen and Eskerod, (2009)
10	Predicting stakeholders' potential influence on the project	Pajunen, (2006); Chinyio and Akintoye, (2008); Jepsen and Eskerod, (2009)
11	Identifying and analyzing possible conflicts and coalitions among stakeholders	Jepsen and Eskerod, (2009); Yang <i>et al.</i> , (2009)
12	Resolving conflicts among stakeholders effectively	Yang <i>et al.</i> , (2009)
13	Managing the change of stakeholders' interests	Jergeas <i>et al.</i> , (2000); Jepsen and Eskerod, (2009)
14	Managing the change of stakeholders' influence	Jergeas <i>et al.</i> , (2000); Olander (2006)
15	Managing the change of relationship among stakeholders	Pajunen, (2006); Chinyio and Akintoye, (2008)
16	Managing change of stakeholders' attributes	Olander (2006)
17	Managing how project decisions affect stakeholders	Chinyio and Akintoye, (2008)
18	Predicting stakeholders' likely reactions for implementing project decisions	Chinyio and Akintoye, (2008); Yang <i>et al.</i> , (2009)
19	Involving relevant stakeholders to redefine (refine) project mission	Jerges <i>et al.</i> , (2000); Yang <i>et al.</i> , (2009)
20	Formulating appropriate strategies to manage/engage different stakeholders	Chinyio and Akintoye, (2008); Yang <i>et al.</i> , (2009)
21	Keeping and promoting positive relationships among the stakeholders	Olander and Landin, (2008); Yang <i>et al.</i> , (2009)
22	Communicating with stakeholders properly and frequently (instituting feedback mechanisms)	Jerges <i>et al.</i> , (2000); Olander and Landin, (2008); Chinyio and Akintoye, (2008); Yang <i>et al.</i> , (2009)
23	Considering corporate social responsibilities (paying attention to economic, legal, environmental and ethical issues)	Mathur <i>et al.</i> , (2008); Yang <i>et al.</i> , (2009)

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

828 **Table 2 Constructs and indicators of conceptual measurement model of CSFs for**
829 **stakeholder management in construction**

Constructs		Indicators
Stakeholder characteristics and project characteristics (SCPC)		<ul style="list-style-type: none">• Clearly formulating the project mission;• Ensuring the use of a favourable procurement method;• Carefully identifying and listing the project stakeholders;• Ensuring flexible project organisation;• Identifying and understanding stakeholders’ areas of interests in the project.
Stakeholder analysis (SA)		<ul style="list-style-type: none">• Determining and assessing the power (capacity to influence the actions of other stakeholders); urgency (degree to which stakeholders’ claims requires immediate attention); legitimacy (perceived validity of claims); and proximity (level of association or closeness with the project) of stakeholders;• Appropriately classifying stakeholders according to their attributes/characteristics;• Predicting and mapping stakeholders’ behaviours (supportive, opposition, neutral etc);• Predicting stakeholders’ potential influence on each other;• Predicting stakeholders’ potential influence on the project;• Identifying and analyzing possible conflicts and coalitions among stakeholders;
Stakeholder	dynamics (SD)	<ul style="list-style-type: none">• Resolving conflicts among stakeholders effectively;• Managing the change of stakeholders’ interests;• Managing the change of stakeholders’ influence;• Managing the change of relationship among stakeholders;• Managing change of stakeholders’ attributes;• Managing how project decisions affect stakeholders;• Predicting stakeholders’ likely reactions for implementing project decisions.
Stakeholder engagement/empowerment (SE)		<ul style="list-style-type: none">• Involving relevant stakeholders to redefine (refine) project mission;• Formulating appropriate strategies to manage/engage different stakeholders;• Keeping and promoting positive relationships among the stakeholders;• Communicating with stakeholders properly and frequently (instituting feedback mechanisms);• Considering corporate social responsibilities (paying attention to economic, legal, environmental and ethical issues).

830

831 **Table 3 Respondents' profiles**

Professional Field	Years of Professional Experience				Total	%Total
	From 6 to 10 years	From 11 to 15 years	From 16 to 20 years	From 21 years and above		
Architecture	5	4	1	2	12	19.67
Construction Management	1	6	3	8	18	29.51
Quantity Surveying	3	3	3	5	14	22.95
Engineering	3	3	1	3	10	16.39
Facility Management	1	3	1	2	7	11.48
Total	13	19	9	20	61	100
%Total	21.31	31.15	14.75	32.79	100	

832

833 **Table 4 Mean rating and ranking of Critical Success Factors for Stakeholder**834 **Management**

Code	Critical Success factors for Stakeholder Management	Mean ^a	Rank
SE1	Involving relevant project stakeholders at the inception stage and whenever necessary to refine project mission	4.43	1
SCPC5	Identifying and understanding stakeholders' areas of interests in the project	4.33	2
SE4	Communicating with stakeholders properly and frequently	4.33	2
SD6	Managing how project decisions affect stakeholders	4.30	4
SD1	Resolving conflicts among stakeholders effectively	4.28	5
SE3	Keeping and promoting positive relationships among stakeholders	4.21	6
SCPC3	Carefully identifying and listing the project stakeholders from the on set	4.18	7
SCPC1	Clearly formulating the project mission	4.15	8
SCPC2	Ensuring the use of a favourable procurement route	4.13	9
SA6	Identifying and analysing possible conflicts and coalitions among stakeholders	4.11	10
SD7	Predicting stakeholders' likely reactions for implementing project decisions	4.07	11
SE2	Formulating appropriate strategies to manage/engage different stakeholders	4.07	11
SA5	Predicting stakeholders' potential influence on the project	4.03	13
SD3	Managing the change of stakeholders' influence	4.03	13
SA1	Determining and assessing the attributes (Power, Urgency, Legitimacy and proximity) of stakeholders in/to the project	4.03	15

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

Code	Critical Success factors for Stakeholder Management	Mean ^a	Rank
SE5	Considering corporate social responsibilities (paying attention to Economic, legal, environmental, and ethical issues)	4.03	15
SA2	Appropriately classifying stakeholders according to their attributes	4.03	15
SD4	Managing the change of relationship among stakeholders	4.02	18
SD2	Managing the change of stakeholders' interests	4.00	19
SA3	Predicting and mapping stakeholders' behaviours (Supportive, Opposition, Neutral, etc)	3.95	20
SA4	Predicting stakeholders' potential influence on each other	3.93	21
SD5	Managing change of stakeholders' attributes	3.92	22
SCPC4	Ensuring the use of flexible project organisation	3.85	23

Notes: ^a: 1= Strongly Disagree and 5= Strongly Agree.

Table 5 Result of GOF measures for both Conceptual and best fitting measurement models of the CSFs for stakeholder management in construction

Goodness-of-fit (GOF) measures	Recommended level of GOF measures	Conceptual measurement model	Best fitting measurement model
CMIN/DF	1 (very good) – 2 (threshold)	1.41	1.18
Root mean sq. Error of approx. (RMSEA)	>0.05 (Very good) – 0.1 (threshold)	0.08	0.05
Root mean sq. Residual (RMR)	0 – 1 (Smaller values = better fit)	0.44	0.35
Goodness-of-fit index (GFI)	0 (no fit) – 1 (perfect fit)	0.72	0.82
Comparative-fit index (CFI)	0 (no fit) – 1 (perfect fit)	0.83	0.95
Incremental-fit index (IFI)	0 (no fit) – 1 (perfect fit)	0.84	0.95
Tucker-Lewis index (TLI)	0 (no fit) – 1 (perfect fit)	0.80	0.94

Table 6 Standardised path coefficients of observed variables' loading on latent variables

Latent variables and their indicators ^a	Standardised path coefficients
Stakeholder Characteristics and Project Characteristics (SCPC)^b	
SCPC2	+0.54
SCPC3	+0.59
SA1	+0.55
SA2	+0.67
SE1	+0.65
Stakeholder Analysis (SA)^b	
SA3	+0.68
SA4	+0.75
SA5	+0.70
SA6	+0.64
Stakeholder Dynamics (SD)^b	

	SD2	+0.78
	SD3	+0.89
	SD4	+0.75
	SD6	+0.76
Stakeholder Engagement/Empowerment (SE)^b		
	SE2	+0.69
	SE3	+0.72
	SE5	+0.68

Note: The path coefficients are all statistically significant at level $P < 0.05$;

^a: refer to Table 1 for full meanings of the indicators; ^b: Latent variables

Table 7 Realigned critical success factors for stakeholder management in construction projects

Realignment ^a	Critical Success Factors for Stakeholder Management	
	Final CSFs Code	Final SCFs
SE1 + SCPC1	SE1	Involving relevant project stakeholders at the inception stage and whenever necessary to formulate and refine project mission
SE3	SE3	None
SCPC3 + SCPC5	SCPC3	Carefully identifying and listing the project stakeholders and their areas of interests from the on set
SCPC2 + SCPC4	SCPC2	Ensuring the use of a favourable procurement route and flexible project organisation
SA6 + SD1	SA6	Identifying, analysing and resolving possible conflicts and coalitions among stakeholders
SE2 + SE4	SE2	Formulating appropriate communication strategies to manage/engage different stakeholders
SA5	SA5	None
SD3	SD3	None
SA1	SA1	None
SE5	SE5	None
SA2	SA2	None
SD4 + SD6	SD4	Managing the change of relationship among stakeholders and how project decisions affect them
SD2	SD2	None
SA3 + SD7	SA3	Predicting and mapping stakeholders' behaviours (Supportive, Opposition, Neutral, etc) and reactions for implementing project decisions
SA4	SA4	None
SD5	SD5	None

Note: ^a: affected CSFs are presented in bold in the first column

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

840
841

Table 8 Standardised correlation and covariance coefficients of the best fitting measurement model of CSFs for stakeholder management in construction

	Covariance links		Correlation Estimate	Covariance Estimate	S.E.	C.R.	Sig(P)
SCPC	<-->	SA	+0.773	0.147	0.049	2.980	0.003
SCPC	<-->	SD	+0.696	0.187	0.061	3.069	0.002
SCPC	<-->	SE	+0.768	0.135	0.046	2.963	0.003
SA	<-->	SD	+0.782	0.212	0.064	3.319	***
SA	<-->	SE	+0.730	0.130	0.044	2.963	0.003
SD	<-->	SE	+0.579	0.145	0.051	2.835	0.005

*** Sig(P) value is infinitesimally small (close to zero) hence cannot be reported

843
844

Table 9 Standardised path coefficients of the conceptual structural model of the interrelations among CSFs for stakeholder management in construction

	Hypothesised relationships		Path coefficient	S.E.	C.R.	Sig(P)	Interpretation
H1:PS	<---	SCPC	+0.012	0.389	0.040	0.968	Not supported
H2:SA	<---	SCPC	+0.772	0.244	3.165	0.002	Supported
H3:SD	<---	SCPC	+0.255	0.372	0.991	0.322	Not supported
H4:PS	<---	SA	-0.125	0.435	0.357	0.721	Not supported
H5:SE	<---	SA	+0.393	0.332	1.069	0.285	Not supported
H6:PS	<---	SD	+0.041	0.283	0.123	0.902	Not supported
H7:SD	<---	SA	+0.608	0.391	2.249	0.025	Supported
H8:SE	<---	SD	+0.634	0.117	3.507	***	Supported
H9:PS	<---	SE	+0.695	0.346	2.667	0.008	Supported
H10:SE	<---	SCPC	+0.528	0.324	1.503	0.133	Not supported

*** Sig(P) value is infinitesimally small (close to zero) hence cannot be reported

Table 10 Result of GOF measures for both Conceptual and best fitting structural models


Goodness-of-fit (GOF) measures	Recommended level of GOF measures	Conceptual structural model	Best fitting structural model
CMIN/DF	1 (very good) – 2 (threshold)	1.27	1.24
Root mean sq. Error of approx. (RMSEA)	>0.05 (Very good) – 0.1 (threshold)	0.07	0.06
Root mean sq. Residual (RMR)	0 – 1 (Smaller values = better fit)	0.05	0.04
Goodness-of-fit index (GFI)	0 (no fit) – 1 (perfect fit)	0.77	0.82
Comparative-fit index (CFI)	0 (no fit) – 1 (perfect fit)	0.90	0.92
Incremental-fit index (IFI)	0 (no fit) – 1 (perfect fit)	0.91	0.92
Tucker-Lewis index (TLI)	0 (no fit) – 1 (perfect fit)	0.89	0.90

List of Figures

- Figure 1 Conceptual Measurement Model of CSFs for Stakeholder Management in Construction
- Figure 2 Hypothesised structural model of critical success factors for stakeholder management in construction
- Figure 3 the Best Fit Measurement Model of CSFs for SM in Construction

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

856 Figure 4 Final structural model of critical success factors for stakeholder management in
857 construction



858
859 Figure 1 Conceptual Measurement Model of CSFs for Stakeholder Management in
860 Construction




Figure 2 Hypothesised Structural Model of Critical Success Factors for Stakeholder Management in Construction

Formatted: Indent: Left: 0"




Figure 3 the Best Fit Measurement Model of CSFs for SM in Construction




Figure 4 Final Structural Model of Critical Success Factors for Stakeholder Management in Construction

Appendix A: Un-rotated principal component analysis of critical success factors for stakeholder management in construction projects.

Component Matrix²

Factor	Component					
	1	2	3	4	5	6
SCPC1	.351	.593	-.219	.525	-.307	.279
SCPC2	.385	-.032	-.459	.682	.457	.315
SCPC3	.488	.145	.684	-.082	.064	-.211
SCPC4	.131	-.454	.584	-.347	.368	.407
SCPC5	.536	.177	.552	.258	-.080	-.138
SA1	.427	-.097	-.267	.267	.417	-.510
SA2	.512	-.227	.174	.498	.233	-.160
SA3	.625	-.357	.223	-.060	.096	.094

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

SA4	.677	-.219	.158	.205	-.011	.201
SA5	.645	-.121	.356	.271	-.217	-.060
SA6	.671	.088	-.136	.279	.017	.341
SD1	.479	.613	.265	-.219	-.086	.208
SD2	.742	-.045	-.138	-.027	-.338	.092
SD3	.756	-.246	-.316	-.096	-.348	.010
SD4	.689	-.460	-.118	-.167	-.053	-.107
SD5	.636	-.549	-.069	-.224	-.166	-.051
SD6	.724	.008	-.144	-.322	.175	-.221
SD7	.619	.136	-.136	-.375	-.028	-.227
SE1	.609	.181	-.154	.151	-.180	-.174
SE2	.638	.288	.164	-.580	.193	.014
SE3	.638	.417	.006	-.182	.295	.147
SE4	.510	.550	-.172	-.122	-.003	-.065
SE5	.662	.217	-.037	-.075	.092	.131

Extraction Method: Principal Component Analysis.
a. 6 components extracted.



Total Variance Explained

Component	Initial Eigenvalues			Extraction Sums of Squared Loadings		
	Total	% of Variance	Cumulative %	Total	% of Variance	Cumulative %
1	7.996	34.764	34.764	7.996	34.764	34.764
2	1.960	8.520	43.284	1.960	8.520	43.284
3	1.442	6.269	49.553	1.442	6.269	49.553
4	1.359	5.908	55.461	1.359	5.908	55.461
5	1.204	5.234	60.694	1.204	5.234	60.694
6	1.100	4.783	65.478	1.100	4.783	65.478
7	.998	4.339	69.817			
8	.926	4.027	73.844			
9	.782	3.398	77.242			
10	.773	3.362	80.604			
11	.670	2.912	83.516			
12	.607	2.641	86.157			
13	.507	2.204	88.361			
14	.497	2.161	90.521			
15	.402	1.748	92.270			
16	.376	1.634	93.904			
17	.352	1.529	95.433			
18	.294	1.279	96.712			
19	.225	.976	97.688			
20	.172	.748	98.436			
21	.138	.602	99.037			
22	.112	.487	99.524			
23	.109	.476	100.000			

Extraction Method: Principal Component Analysis.

874

875

876

877

For Peer Review